

## MATERIAL SAFETY DATA SHEET EZ-SNAP

1. Product And Company Identification	
<b>Supplier</b> Serious Energy, Inc 1250 Elko Dr Sunnyvale, CA 94089  <b>Telephone Number:</b> 408-541-8000 <b>FAX Number:</b> 408-715-2560 <b>E-Mail:</b> support@seriousenergy.com <b>Web Site:</b> www.seriousenergy.com	<b>Manufacturer</b> Serious Energy, Inc 1250 Elko Dr Sunnyvale, CA 94089  <b>Telephone Number:</b> 408-541-8000 <b>FAX Number:</b> 408-715-2560 <b>E-Mail:</b> support@seriousenergy.com <b>Web Site:</b> www.seriousenergy.com
<b>Supplier Emergency Contacts &amp; Phone Number</b> Safety Officer – 408-541-8000	<b>Manufacturer Emergency Contacts &amp; Phone Number</b> Safety Officer – 408-541-8000
<b>Issue Date:</b> 10/05/2009 <b>Revision Date:</b> 6/24/2011  <b>Product Name:</b> QuietRock ES and QuietRock ES Mold Resistant <b>MSDS Number:</b> QR0708-B  <b>Product Code:</b> QR-ES, QR-ES MR <b>Product/Material Uses</b> - Multi-layer soundproof drywall.	

2. Composition/Information on Ingredients		
Ingredient Name	CAS Number	Percent of Total Weight
Gypsum (Calcium Sulfate Dihydrate)	10101-41-4	> 80
Cellulose	9004-34-6	< 10
Paraffin Wax	mixture	< 10
Vermiculite	1318-00-9	< 10
Starch	9005-25-8	< 3
Proprietary Polymers	confidential	< 3
Rosin Ester	confidential	< 3
Quartz (Crystalline Silica)	14808-60-7	< 3
Fiberglass	65997-17-3	< 2
N,N dimethylethanolamine	108-01-0	< 1
Barium metaborate monohydrate	13701-59-2	< 0.2
Sodium o-phenylphenate	132-27-4	trace
2-(Thiocyanomethylthio)benzothiazole (TCMTB)	21564-17-0	trace

EMERGENCY OVERVIEW
<b>CAUTION:</b> Dust generated from cutting, sanding, grinding, machining or sawing may cause irritation of the upper respiratory tract, eyes and skin. Use exposure controls or personal protection methods described in Section 8.

## 3. Hazards Identification

**Likely Routes of Exposure:** Skin contact, eye contact, and inhalation.

### EFFECTS OF OVEREXPOSURE

#### **Potential Health Effects:**

**Eye Hazards** – Exposure to airborne dust may cause immediate or delayed mechanical irritation of eyes.

**Skin Hazards** – Dust and glass fibers may produce dryness, itching, rash and redness. Frequent exposure may have a drying effect on skin.

**Ingestion Hazards** – Not applicable under normal conditions of use. May result in internal discomfort or ill effects if large quantities are swallowed.

**Inhalation Hazards** – Exposure to airborne dust generated during the handling or use of the product may cause irritation to nose, throat and upper respiratory system. Pre-existing upper respiratory and lung diseases may be aggravated. Prolonged inhalation of dust may cause lung disease such as silicosis due to the presence of free crystalline silica. Exposures to respirable crystalline silica have not been documented during normal use of this product. However, good housekeeping practices and industrial hygiene monitoring is recommended when the potential for significant exposure exists. During demolition, TCMTB in the paper may become airborne.

**Medical Conditions Aggravated By Exposure:** Because of irritating properties, dust and glass fibers may aggravate preexisting skin, eye, and respiratory conditions.

**Target Organs:** Skin, eyes and respiratory system

## 4. First Aid Measures

**Eye:** Immediately flush eye thoroughly with water for at least 15 minutes. Remove contact lenses (if applicable). Seek medical attention if irritation persists.

**Skin:** Wash skin with mild soap and plenty of water. Seek medical treatment if irritation develops and persists.

**Ingestion:** Not known. May result in obstruction and irritation if ingested. Seek medical attention.

**Inhalation:** Remove to fresh air. Seek medical attention if symptoms persist.

## 5. Fire Fighting Measures

**Flammability Class:** Non-Flammable by OSHA/WHMIS criteria.

**Products of Combustion:** Above 1450°C, gypsum will decompose to calcium oxide with releases of sulfur dioxide and various oxides of carbon.

**Fire And Explosion Hazards:** None. Not combustible.

**Extinguishing Media:** Use the appropriate extinguishing media for the surrounding fire. Dry chemical, foam, water, fog or spray.

**Fire Fighting Instructions:** None. Although, gypsum panels pose no fire related hazards, firefighters should wear full protective clothing including self contained breathing apparatus. Water can be used to cool and protect exposed material.

## 6. Accidental Release Measures

- Not applicable, as product is an article composite.
- Collect panels from spillage and if not damaged or contaminated by foreign material, panels may be reclaimed.

### General recommendations:

- Use exposure control and appropriate personal protective equipment (See Section 8).
- Pick-up larger pieces to avoid a tripping hazard. Sweep or vacuum remaining material into a waste container for disposal. Use a light water spray to minimize dust generation.
- Dispose of in accordance with applicable federal, state and local regulations.

## 7. Handling And Storage

### **Handling And Storage Precautions**

- Store material in a cool, dry, ventilated area. Do not use when temperatures exceed 125°F.
- Stack or store all panels flat to minimize damage and warping.
- Do not stack panels too high when storing to minimize the risk of falling.
- Panels are heavy and can fall over, causing serious injury or death. Do not stack panels too high.

- Utilize proper lifting techniques when moving product and employ mechanical/ergonomic assistance when possible (i.e. move with forklifts, hold in place with lifts) to minimize the risk of back injury.
- Scoring and snapping is the method to be used when cutting the panels in order to reduce dust generation.
- Use exposure control and appropriate personal protect equipment (See Section 8).

## 8. Exposure Control/Personal Protection

**Engineering Controls:** The score and snap method of cutting is recommended. Sawing, drilling or machining will produce dust. Use with adequate general and local exhaust ventilation to maintain a dust level below the PEL/TLV.

**Eye/Face Protection:** Safety glasses with side shields or goggles.

**Skin Protection:** Wear protective gloves. Protective clothing to prevent skin contact is recommended.

**Respiratory Protection:** General room ventilation is normally adequate. In case of inadequate ventilation, use a NIOSH-approved respirator for particulates (eg. N95). OSHA's 29 CFR 1910.134 (Respiratory Protection Standard) must be followed whenever work conditions require respirator use.

**Ingredient(s) - Exposure Limits:**

Component	OSHA PEL (mg/m <sup>3</sup> )	ACGIH TLV (mg/m <sup>3</sup> )
Calcium Sulfate Dihydrate (Gypsum)	15 <sup>(T)</sup> 5 <sup>(R)</sup>	10 <sup>(T)</sup>
Cellulose (Paper Fiber)	15 <sup>(T)</sup> 5 <sup>(R)</sup>	10 <sup>(T)</sup>
Starch	15 <sup>(T)</sup> 5 <sup>(R)</sup>	10 <sup>(T)</sup>
Vermiculite	15 <sup>(T)</sup> 5 <sup>(R)</sup>	5
Paraffin Wax	2 (fume)	2 (fume)
Crystalline Silica (Quartz)	30 <sup>(T)</sup> 10 <sup>(R)</sup>	0.025 <sup>(R)</sup>
Fiberglass scrim, synthetic, vitreous, continuous	15 <sup>(T)</sup> 5 <sup>(R)</sup>	1 f/cc <sup>(R)</sup>
Barium metaborate monohydrate		TWA: 0.5

T - Total Dust

R - Respirable Dust

## 9. Physical And Chemical Properties

**Appearance:** Paper covered panel with white core

**Odor:** Low odor

**Physical State:** Solid

**Density:** approximately 50 lbs/ft<sup>3</sup>

**Evaporation:** Not applicable

**Flash Point:** None

**Auto Ignition Temperature:** Not combustible

**Decomposition Temp:** 1450°C

**Solubility in Water (% by wt.):** approximately 0.2 gs/100cc

## 10. Stability And Reactivity

**Stability:** Stable.

**Conditions to Avoid:** High relative humidity will cause panels to deteriorate.

**Hazardous Polymerization:** Will not occur.

**Incompatible Materials:** Reaction with strong acids will generate carbon dioxide.

**Hazardous Decomposition Products:** Above 1450°C, gypsum will decompose to calcium oxide with releases of sulfur dioxide and various oxides of carbon.

## 11. Toxicological Information

In general, no adverse health effects are expected if product is handled as recommended with suitable precautions for designated uses.

### EFFECTS OF ACUTE EXPOSURE

#### Component Analysis

Ingredient	LD <sub>50</sub> (oral)	LC <sub>50</sub> (inhalation)
Calcium sulfate dihydrate	2,000 mg/kg (female rat)	Not available
Crystalline Silica (Quartz)	Not available	Not available
Barium metaborate monohydrate	850 mg/kg (male rat)	≥ 2.54 mg/l (4 hrs, rat)

### EFFECTS OF CHRONIC EXPOSURE

**Chronic Effects:** Hazardous by OSHA/WHMIS criteria. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. Chronic ingestion of some barium compounds may have an adverse effect on the cardiovascular system.

**Carcinogenicity:** Hazardous by OSHA/WHMIS criteria

**Mutagenicity; Reproductive Effects: Teratogenicity; Embryotoxicity; Respiratory Sensitization; Skin Sensitization:** Not hazardous by OSHA/WHMIS Criteria, Boron compounds have been associated with reproductive effects in animal studies.

**Toxicologically Synergistic Materials:** Not Available.

**Target Organs:** Lungs

#### Ingredient

Crystalline silica (quartz)

**ACGIH** – A2 – Suspected human carcinogen

**IARC** – 1 – The agent is carcinogenic to humans

**NTP** – 1 – Known to be carcinogens

**Toxicologically Synergistic Materials:** Not Available.

## 12. Ecological Information

**Aquatic Toxicity:** Unknown. Not believed to be toxic.

**Other Environmental Information:** Unknown.

## 13. Disposal Considerations

Dispose of according to federal, state and local government regulations. Recycle if possible.

**RCRA Information** - Product is not a RCRA Hazardous Waste.

## 14. Transport Information

**Proper Shipping Name** - Not regulated.

## 15. Regulatory Information

**SARA Title III:** Not listed under Sections 302 and 304. This product contains substances classified as a delayed (chronic) health hazard under Sections 311 – 312. Barium metaborate monohydrate is included in the Toxic Chemical List and subject to reporting under section 313.

**OSHA:** Dust and potential respirable crystalline silica generated during product use may be hazardous.

**Ingredient(s) – Canadian Regulatory Information:** Crystalline silica: WHMIS Classification D2A.

All components of this product are included in the Canadian Domestic Substances List (DSL).

**Toxic Substances Control Act (TSCA):** All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30.

**California Safe Drinking Water and Toxic Enforcement Act (Prop. 65):** This product may contain substance(s) which are known to the State of California to cause cancer or reproductive harm. Respirable crystalline silica is known to the state of California to cause cancer.

A small amount of barium metaborate monohydrate (Busan 11-M1) is added for mold resistance. This material is registered under the EPA as pesticide, Registration No: 1448-17-AA. CA Pesticide Product ID No: 6030.

## 16. Other Information

### **NFPA Rating**

Health: 1

Fire: 0

Reactivity: 0

### **HMIS Rating**

Health: 1

Fire: 0

Reactivity: 0

Personal Protection: E

### **WHMIS Classification(s)**

Class D2A – Carcinogenicity

Class D2A – Chronic Toxic Effects

### **Reference Documentation**

The following were the primary references used in the creation of this MSDS:

- Canadian Center for Occupational Health & Safety (CCINFO) MSDS Database
- Guide to Occupational Exposure Values, ACGIH 2002-2003
- U.S. National Library of Medicine Hazardous Substance Databank (HSDB)
- Registry Toxic Effects of Chemical Substances (RTECS)

## Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

Serious Energy, Inc.