

SAFETY DATA SHEET

1. Identification

Product identifier	Paper Faced Gypsum Panels
Other means of identification	
Product code	GP-71A
Synonyms	See Product List found in Section 16
Recommended use	Products accommodate wide range of wall, floor and ceiling applications and soffit treatments.
Recommended restrictions	Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Company name	Georgia-Pacific Gypsum LLC		
Address	133 Peachtree Street, NE Atlanta, GA 30303		
Telephone	Technical Information	800.225.6119	
	(M)SDS Request	404.652.5119	
E-mail	Not available.		
Emergency phone number	Chemtrec - Emergency	800.424.9300	

2. Hazard(s) identification

Emergency overview	This product is not hazardous in the form in which it is shipped by the manufacturer but may become hazardous by downstream activities such as cutting, sanding, or otherwise working with this product that generate large amount of dusts. Those hazards associated with large amount of dusts are described below.		
Physical hazards	Not classified.		
Health hazards	Serious eye damage/eye irritation	Category 2B	
Environmental hazards	Not classified.		
OSHA defined hazards	Not classified.		
Label elements			
Hazard symbol	None.		
Signal word	Warning		
Hazard statement	Causes eye irritation.		
Precautionary statement			
Prevention	Observe good industrial hygiene practices. Wash thoroughly after handling.		
Response	Wash hands after handling. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.		
Storage	Store away from strong acids.		
Disposal	Dispose of waste and residues in accordance with local authority requirements.		
Hazard(s) not otherwise classified (HNOC)	None known.		
Supplemental information	None.		

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
CALCIUM SULFATE DIHYDRATE		10101-41-4	60 - 100
VERMICULITE****		1318-00-9	0 - 3
CRYSTALLINE SILICA (QUARTZ)*		14808-60-7	0.1 - 1

Chemical name	Common name and synonyms	CAS number	%
BORIC ACID**		10043-35-3	0 - 1
CONTINUOUS FILAMENT GLASS FIBERS***		65997-17-3	0 - 1

Composition comments

** Found in products in List B, C and F, Section 16 of this SDS.
 *** Found in products in List C, D, E and F, Section 16 of this SDS.
 **** Found in products in List E and F, Section 16 of this SDS.

Gypsum (calcium sulfate, dihydrate) contains naturally occurring silica crystalline (quartz), which is listed as a lung carcinogen. See Section 8 for exposure information.

*The weight percent for crystalline silica represents total crystalline silica and not the respirable fraction. Testing conducted by Georgia-Pacific did not detect respirable crystalline silica during activities associated with the normal use of this product; however, jobsite air monitoring should be conducted to determine actual exposure when permissible exposure limits may be exceeded.

**Testing conducted by Georgia-Pacific did not detect boric acid during activities associated with the normal use of this product; however, jobsite air monitoring should be conducted to determine actual exposure when permissible exposure limits may be exceeded.

4. First-aid measures

Inhalation

If dust from the material is inhaled, remove the affected person immediately to fresh air. Call a physician if symptoms develop or persist.

Skin contact

For skin contact, wash immediately with soap and water. Get medical attention if irritation develops and persists.

Eye contact

Do not rub the eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion

Rinse mouth. May result in obstruction and irritation if ingested. Get medical attention.

Most important symptoms/effects, acute and delayed

Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

None known.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions

Firefighters should wear full protective clothing including self contained breathing apparatus.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Use personal protection recommended in Section 8. Keep unnecessary personnel away. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits.

Methods and materials for containment and cleaning up

Minimize dust generation. Sweep up or gather material and place in an appropriate container for disposal. Utilize wet methods, if appropriate, to minimize dust. For waste disposal, see section 13 of the SDS.

Environmental precautions

Keep out of drains, sewers, ditches, and waterways.

7. Handling and storage

Precautions for safe handling

Provide appropriate exhaust ventilation at places where dust is formed. Minimize dust generation and accumulation. Do not breathe dust. Do not get this material in contact with eyes. Do not taste or swallow. Avoid prolonged exposure. Observe good industrial hygiene practices. Use only in well-ventilated areas. Wear appropriate NIOSH approved dust mask or filtering facepiece if dust is generated. Do not eat or drink while using the product. Wash hands before eating, drinking, or smoking.

Conditions for safe storage, including any incompatibilities

Store level and keep dry. Dewpoint or other conditions causing the presence of moisture can damage the product during storage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US OSHA Table Z-3: Calculated Time Weighted Average (TWA) (mg/m³)

Components	Type	Value	Form
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	TWA	8.6 mg/m ³	Total dust.
		2.9 mg/m ³	Respirable.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4)	PEL	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.
VERMICULITE**** (CAS 1318-00-9)	PEL	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.

US ACGIH Threshold Limit Values: Short Term Exposure Limit (STEL): mg/m³

Components	Type	Value	Form
BORIC ACID** (CAS 10043-35-3)	STEL	6 mg/m ³	Inhalable fraction.

US ACGIH Threshold Limit Values: Time Weighted Average (TWA): mg/m³, non-standard units

Components	Type	Value	Form
BORIC ACID** (CAS 10043-35-3)	TWA	2 mg/m ³	Inhalable fraction.
CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4)	TWA	10 mg/m ³	Inhalable fraction.
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	TWA	0.025 mg/m ³	Respirable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4)	TWA	5 mg/m ³	Respirable.
		10 mg/m ³	Total
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	TWA	0.05 mg/m ³	Respirable dust.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines	Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled. Exposure limits for CRYSTALLINE SILICA - The US OSHA exposure limits 8 hour TWA for CRYSTALLINE SILICA (QUARTZ) are calculated from the following equations: $30/(\%SiO_2+2)$ mg/m ³ for total dust; and $10/(\%SiO_2+2)$ mg/m ³ for the respirable fraction. *Testing conducted by Georgia-Pacific did not detect respirable crystalline silica during activities associated with the normal use of this product; however, jobsite air monitoring should be conducted to determine actual exposure when permissible exposure limits may be exceeded. **Testing conducted by Georgia-Pacific did not detect boric acid during activities associated with the normal use of this product; however, jobsite air monitoring should be conducted to determine actual exposure when permissible exposure limits may be exceeded.
Appropriate engineering controls	Score and snap method recommended. When using product, provide local and general exhaust ventilation to keep airborne dust concentrations below exposure limits. Use wet methods, if appropriate, to reduce the generation of dust. Ventilation should be sufficient to effectively remove and prevent buildup of any dusts or fumes that may be generated during handling or thermal processing. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Safety glasses or goggles are recommended when using this product. Ensure compliance with OSHA's PPE standard (29 CFR 1910.132 and .133) for eye and face protection.
Skin protection	
Hand protection	For prolonged or repeated skin contact use suitable protective gloves.
Other	Impervious protective clothing and gloves recommended to prevent drying or irritation of skin. Ensure compliance with OSHA's PPE standards (29 CFR 1910.132 (general) and 138 (hand protection)). Safety shower/eye wash fountain is recommended in the workplace area (29 CFR 1910.151 (c)).
Respiratory protection	A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).
Thermal hazards	Not applicable.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Paper faced gypsum boards
Physical state	Solid.
Form	Solid.
Color	Facing color varies
Odor	Odorless
Odor threshold	Not available.
pH	7
Melting point/freezing point	2642 °F (1450 °C) estimated
Initial boiling point and boiling range	Not applicable
Flash point	Not applicable
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not applicable
Flammability limit - upper (%)	Not applicable
Explosive limit - lower (%)	Not available.

Explosive limit - upper (%)	Not available.
Vapor pressure	Not applicable
Vapor density	Not applicable
Relative density	2.2 - 2.4 g/cm ³
Solubility(ies)	
Solubility (water)	0.2 % @ 22°C
Partition coefficient (n-octanol/water)	Not applicable
Auto-ignition temperature	Not applicable
Decomposition temperature	Not available.
Viscosity	Not applicable
Other information	
Flash point class	Not flammable
Specific gravity	2.2 - 2.4

10. Stability and reactivity

Reactivity	Contact with strong acids produces carbon dioxide.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).
Incompatible materials	Strong acids.
Hazardous decomposition products	May include and are not limited to: calcium oxide and sulfur dioxide.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Not applicable under normal conditions of use. May cause gastrointestinal irritation if ingested.
Inhalation	Inhalation of dusts may cause respiratory irritation.
Skin contact	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Eye contact	Dust in the eyes will cause irritation.

Symptoms related to the physical, chemical and toxicological characteristics Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
BORIC ACID** (CAS 10043-35-3)		
Acute		
<i>Inhalation</i>		
LC50	Rat	> 2 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	2660 mg/kg
CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4)		
Acute		
<i>Oral</i>		
LD50	Rat	> 1581 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Dust in the eyes will cause irritation.

Respiratory or skin sensitization

Respiratory sensitization Not likely to cause respiratory sensitization.

Skin sensitization This product is not expected to cause skin sensitization.
Germ cell mutagenicity Not classified.
Carcinogenicity Not expected to be hazardous by OSHA criteria.

Exposure to respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by IARC and NTP as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to a respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of respirable crystalline silica exposure and the length of time (usually years) of exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity Not classified.
Specific target organ toxicity - single exposure Not classified.
Specific target organ toxicity - repeated exposure Not classified.
Aspiration hazard Not classified.
Chronic effects Not hazardous under normal conditions of use.

12. Ecological information

Ecotoxicity Not considered to be harmful to aquatic life.

Product	Species	Test Results
Paper Faced Gypsum Panels		
Aquatic		
<i>Acute</i>		
Fish	LC50	2049.4597 mg/l, 96 hours estimated
Components	Species	Test Results
BORIC ACID** (CAS 10043-35-3)		
Aquatic		
Crustacea	EC50	766.5 mg/L, 48 Hours
Fish	LC50	Razorback sucker (<i>Xyrauchen texanus</i>) > 100 mg/l, 96 hours
CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) > 1970 mg/l, 96 hours
CONTINUOUS FILAMENT GLASS FIBERS*** (CAS 65997-17-3)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Zebra danio (<i>Danio rerio</i>) > 1000 mg/l, 96 hours ECHA
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Zebra danio (<i>Danio rerio</i>) > 10000 mg/l, 96 Hours OECD SIDS

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations.
Contaminated packaging	Not available.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US federal regulations This product is not hazardous in the form in which it is sold and shipped by the manufacturer. However, the large amount of dusts generated by downstream activities such as cutting, sanding, or otherwise working with this product is considered hazardous and is regulated under the Hazard Communication Standard 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4)
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)

US. New Jersey Worker and Community Right-to-Know Act

CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4)
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)

US. Pennsylvania Worker and Community Right-to-Know Law

CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4)
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Product list	Product List A ToughRock® Veneer Plaster Base (Blueboard) ToughRock® Flexroc® Gypsum Board ToughRock® Mold-Guard™ Gypsum Board ToughRock® Basement Board® Gypsum Board ToughRock® Sound Deadening Gypsum Board ToughRock® Stretch 54® Gypsum Board ToughRock® Soffit Board Product List B ToughRock® Gypsum Board Product List C ToughRock® Span 24® Lite-Weight Ceiling Board ToughRock® Stretch 54® Lite-Weight Gypsum Board ToughRock® Lite-Weight Gypsum Board ToughRock® MH Ceiling Board ToughRock® Fireguard X™ Gypsum Board Product List D ToughRock® Gypsum Sheathing ToughRock® Span 24® Ceiling Board ToughRock® Fireguard X™ Gypsum Sheathing ToughRock® Fireguard X™ Stretch 54® Gypsum Board ToughRock® Fireguard X™ Mold-Guard™ Abuse-Resistant Gypsum ToughRock® Fireguard X™ Veneer Plaster Board ToughRock® Fireguard X™ Soffit Board ToughRock® Fireguard X™ Abuse-Resistant Gypsum Board ToughRock® Fireguard X™ Mold-Guard™ Gypsum Board Product List E ToughRock® Shaftliner ToughRock® Fireguard C® Soffit Board ToughRock® Fireguard C® Stretch 54® Gypsum Board ToughRock® Lite-Weight Fire-Rated Gypsum Board Product List F ToughRock® Fireguard C® Gypsum Board
Issue date	March-13-2015
Revision date	13-Mar-2015

Version # 01
HMIS® ratings Health: 1
Flammability: 0
Physical hazard: 0
NFPA ratings Health: 1
Flammability: 0
Instability: 0

Disclaimer This SDS is intended to quickly provide useful information to the user(s) of this material or product. It is not intended to serve as a comprehensive discussion of all possible risks or hazards, and it assumes a reasonable use of the product. The information contained in this SDS is believed to be accurate as of the date of preparation of this SDS and has been compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. The user or handler (or their employer) should consider the specific conditions in which this material will be used, handled, or stored and determine what specific safety or other precautions are required. Employers should ensure that their employees, agents, contractors, and customers who will use the product receive adequate warnings and safe handling procedures, including a current SDS. Product users or handlers (or their employer) who are unsure of what specific precautions are required should consult their employer, product supplier, or safety or health professionals before handling or working with this product. Please notify us immediately if you believe this SDS or other safety and health information about this product is inaccurate or incomplete.

Revision Information Product and Company Identification: Synonyms
Composition / Information on Ingredients: Ingredients
Physical & Chemical Properties: Multiple Properties
Toxicological Information: Toxicological Data
Ecological Information: Ecotoxicity
Regulatory Information: United States
HazReg Data: North America
Index: United States
GHS: Classification